

**Island mounted
Pureline Frame 120 cm
Black**



EAN 5414425230693

Functions & features

| | |
|--|-------------------------------|
| ▪ Motor | Integrated |
| ▪ Sound absorber | Integrated |
| ▪ Recirculation | Standard, Monoblock |
| ▪ InTouch function | Standard |
| ▪ Auto stop | ▪ |
| ▪ Delayed switch off (minutes) | 30 |
| ▪ Grease filter | 6830020 |
| ▪ Number of grease filters | 2 |
| ▪ Grease filter cleaning indication | ▪ |
| ▪ Recirculation filter cleaning indication | ▪ |
| ▪ Control method | Push buttons + Remote control |
| ▪ Number of speeds | 3 + power |
| ▪ Automatic Power revert (minutes) | 6 |

Dimensions

| | |
|---|------------------------|
| ▪ Product dimensions recirculation (WxDxHmin-Hmax) (mm) | 1172 x 556 x 800 - 800 |
| ▪ Advised mounting height induction hobs (Hmin-Hmax) (mm) | 650 - 850 |
| ▪ Advised mounting height gas hobs (Hmin-Hmax) (mm) | 650 - 850 |
| ▪ Advised mounting height ceramic hobs (Hmin-Hmax) (mm) | 650 - 850 |
| ▪ Position exhaust | Top |

Frame Dimensions

| | |
|---|------------------|
| ▪ Frame Dimensions (WxDxH) (mm) | 25 x 806 x 800 |
| ▪ Number of frames | 2 |
| ▪ Cut-out lower shelf (WxD) (mm) | 1145 x 485 |
| ▪ Dimensions housing cooker hood (WxDxH) (mm) | 1172 x 556 x 330 |
| ▪ Width cut-out top shelf (mm) | 401 |
| ▪ Thickness of shelf material (mm) | 18 - 25 |
| ▪ Depth of shelf material (mm) | 750 |
| ▪ Frame width (mm) | 25 |
| ▪ Frame depth (mm) | 806 |
| ▪ Frame height (mm) | 800 |
| ▪ Width cut-out lower shelf (mm) | 1145 |
| ▪ Depth cut-out lower shelf (mm) | 485 |
| ▪ Width housing cooker hood (mm) | 1172 |
| ▪ Depth housing cooker hood (mm) | 556 |
| ▪ Height housing cooker hood (mm) | 330 |
| ▪ Depth cut-out top shelf (mm) | 248 |
| ▪ Cut-out top shelf (WxD) (mm) | 401 x 248 |

Lighting

| | |
|-----------------------------|-----|
| ▪ Functional lighting type | LED |
| ▪ Functional light dimmable | ▪ |

Lighting

| | |
|---|-----------|
| ▪ Soft-ON/OFF | - |
| ▪ Number of functional lights | 4 |
| ▪ Total energy consumption functional light (W) | 8 |
| ▪ Color functional light (K) | 2700/4000 |

Airflow and noise level

| | |
|---|---------|
| ▪ Free airflow (m ³ /h) | 815 |
| ▪ Airflow (m ³ /h) measured according to EN 61591 | |
| ▪ Sound regulation according to | |
| ▪ Airflow duct out speed 1 (m ³ /h) | 252 |
| ▪ Airflow duct out speed 2 (m ³ /h) | 379 |
| ▪ Airflow duct out speed 3 (m ³ /h) | 445 |
| ▪ Airflow duct out max powerspeed (m ³ /h) (Qboost) | 508 |
| ▪ Sound pressure duct out speed 1 (dB(A)) / Sound power duct out speed 1 (dB(A)) | 35 / 47 |
| ▪ Sound pressure duct out speed 2 (dB(A)) / Sound power duct out speed 2 (dB(A)) | 42 / 54 |
| ▪ Sound pressure duct out speed 3 (dB(A)) / Sound power duct out speed 3 (dB(A)) | 45 / 58 |
| ▪ Sound pressure duct out at max powerspeed (dB(A)) / Sound power duct out at max powerspeed (dB(A)) (LWAboost) | 48 / 61 |

Technical specifications

| | |
|---------------------------------|---------|
| ▪ Maximum power (W) | 117 |
| ▪ Voltage appliance (V) | 220-240 |
| ▪ Frequency (Hz) | 50-60 |
| ▪ Net weight (kg) | 56 |
| ▪ Length power supply cable (m) | 1,8 |

15002 / 15004 / 15006 / 15010 / 15012

