

Wall mounted
Salsa 60 cm
Stainless steel

Energy label

▪ Energy Efficiency class (EEI)	C
▪ Annual Energy Consumption (kWh/year) (AEC _{hood})	85,6
▪ Fluid Dynamic Efficiency class (FDE _{hood})	B
▪ Lighting Efficiency class (LE _{hood})	E
▪ Grease Filtering Efficiency class (GFE _{hood})	D

Functions & features

▪ Control method	Push buttons
▪ Number of speeds	3
▪ Motor	Integrated
▪ Sound absorber	Without
▪ Recirculation	Optional
▪ Auto stop	-
▪ Number of grease filters	1
▪ Grease filter cleaning indication	-
▪ Recirculation filter cleaning indication	-

Dimensions

▪ Product dimensions exhaust (WxDxH _{min} -H _{max}) (mm)	598 x 520 x 710 - 1140
▪ Product dimensions recirculation (WxDxH _{min} -H _{max}) (mm)	598 x 520 x 765 - 1205
▪ Max height optional chimney exhaust (mm)	1460
▪ Max height optional chimney recirculation (mm)	1525
▪ Advised mounting height ceramic hobs (H _{min} -H _{max}) (mm)	600 - 750
▪ Advised mounting height gas and induction hobs (H _{min} -H _{max}) (mm)	650 - 750
▪ Diameter outlet (mm)	150
▪ Position exhaust	Top

Lighting

▪ Functional lighting type	Halogen
▪ Dimmable light	-
▪ Soft-ON/OFF	-
▪ Total energy consumption functional light (W)	40

Airflow and noise level

▪ Airflow (m ³ /h) measured according to EN 61591	
▪ Sound regulation according to EN 60704-2-13	
▪ Airflow speed 1 (m ³ /h)	239
▪ Airflow speed 2 (m ³ /h)	437
▪ Airflow speed 3 (m ³ /h)	602
▪ Sound power speed 1 (dB(A)) / Sound pressure speed 1 (dB(A))	41 / 31
▪ Sound power speed 2 (dB(A)) / Sound pressure speed 2 (dB(A))	55 / 45
▪ Sound power speed 3 (dB(A)) / Sound pressure speed 3 (dB(A))	62 / 52

Technical specifications

- Maximum power 217
- Voltage (V) 220-230
- Frequency (Hz) 50

Installation accessories

Back panel & chimney extensions

- 6200100 Chimney extension
- 140200 Back panel

Accessories

Recirculation kit



6200400

Recirculation Kit

Efficiency Curve
