6921|09

NOVY Technical File

Ceiling unit Novy Pureline Pro Compact 120 cm White

EAN 5414425222087

Energy label

■ Energy Efficiency class (EElhood)		
Annual Energy Consumption (kWh/year) (AEChood)	69,5	
 Fluid Dynamic Efficiency class (FDEhood) 	В	
Lighting Efficiency class (LEhood)	C	
 Grease Filtering Efficiency class (GFEhood) 	D	

Functions & features

• Motor	Integrated
Sound absorber	Integrated
Recirculation	Optional
■ InTouch function	Standard
- Auto stop	
Delayed switch off (minutes)	10
■ Grease filter	6830020
 Number of grease filters 	2
 Grease filter cleaning indication 	
 Recirculation filter cleaning indication 	
 Control method 	Remote control
Novy Connect	Standard
 Number of speeds 	3 + power
Automatic Power revert (minutes)	6

Dimensions

Product dimensions (WxDxH) (mm)	1168 x 508 x 195
Height incl. mounting clamps (without motorbox) (mm)	133
Width flange (mm)	15
Dimensions cut-out opening (WxD) (mm)	1145 x 485
 Advised mounting height induction hobs (Hmin-Hmax) (mm) 	600 - 1600
Advised mounting height gas hobs (Hmin-Hmax) (mm)	650 - 1600
 Advised mounting height ceramic hobs (Hmin-Hmax) (mm) 	600 - 1600
Diameter outlet (mm)	222x89
Position exhaust	Right, Left, Front, Back

Lighting

Functional lighting type	Led strip
 Functional light dimmable 	
Soft-ON/OFF	
 Total energy consumption functional light (W) 	21
Color functional light (K)	2700-5000
Ambient lighting type	Led strip
 Total energy consumption ambient light (W) 	21
Color ambient light (K)	2700-5000

Airflow and noise level

Free airflow (m³/h)	750	
 Airflow (m³/h) measured according to EN 61591 		
Sound regulation according to DIN 45635-2		
Airflow duct out speed 1 (m³/h) / Max pressure duct out speed 1 (Pa)	251 / 50	
Airflow duct out speed 2 (m³/h) / Max pressure duct out speed 2 (Pa)	468 / 187	
Airflow duct out speed 3 (m³/h) / Max pressure duct out speed 3 (Pa)	548 / 267	
Airflow duct out max powerspeed (m³/h) (Qboost) / Max pressure duct	ct out619 / 506	
max powerspeed (Pa)		
Sound pressure duct out speed 1 (dB(A)) / Sound power duct out sp	peed 28 / 41	
1 (dB(A))		
* Sound processed dust out aread 0 (dD(A)) / Sound power dust out on	and 45 / 57	

- $^{\bullet}$ Sound pressure duct out speed 2 (dB(A)) / Sound power duct out speed 45 / 57 2 (dB(A))
- Sound pressure duct out speed 3 (dB(A)) / Sound power duct out speed 50 / 62 3 (dB(A))
- ${}^\bullet$ Sound pressure duct out at max powerspeed (dB(A)) / Sound power duct 51 / 63 out at max powerspeed (dB(A)) (LWAboost)

Technical specifications

Maximum power (W)	210
Voltage appliance (V)	220-240
Frequency (Hz)	50-60
Power consumption in stand-by-mode (Ps) (W)	0.48
Net weight (kg)	22,7
Length power supply cable (m)	1,2

Novy Sense sensor kit • 6910070		Kit Novy Sense sensor Novy Pureline Pro Compact
Accessories		
Recirculation box		
	841400	Exhaust box with monoblock filter
	842400	Exhaust box with monoblock filter
	843400	Exhaust box with monoblock filter
	7931400	Exhaust box with monoblock filter
	7932400	Exhaust box with monoblock filter

Recirculation box with monoblock filter

7933400

^{*} For duct work compatibilities & accessories visit www.novy.com

6921|09

