

**Build under
100 cm
Stainless steel**



EAN 5414425007509

Energy label

▪ Energy Efficiency class (EEIhood)	D
▪ Annual Energy Consumption (kWh/year) (AEChood)	112,3
▪ Fluid Dynamic Efficiency class (FDEhood)	E
▪ Lighting Efficiency class (LEhood)	E
▪ Grease Filtering Efficiency class (GFEhood)	D

Functions & features

▪ Control method	Knobs
▪ Number of speeds	3
▪ Motor	Integrated
▪ Sound absorber	Integrated
▪ Auto stop	-
▪ Number of grease filters	2
▪ Grease filter	906109
▪ Grease filter cleaning indication	-
▪ Recirculation filter cleaning indication	-

Dimensions

▪ Product dimensions (WxDxH) (mm)	998 x 518 x 261
▪ Advised mounting height induction hobs (Hmin-Hmax) (mm)	650 - 750
▪ Advised mounting height gas hobs (Hmin-Hmax) (mm)	650 - 750
▪ Advised mounting height ceramic hobs (Hmin-Hmax) (mm)	600 - 750
▪ Diameter outlet (mm)	2x125
▪ Position exhaust	Top

Lighting

▪ Functional lighting type	TL 8
▪ Dimmable light	-
▪ Soft-ON/OFF	-
▪ Total energy consumption functional light (W)	18

Airflow and noise level

▪ Airflow (m ³ /h) measured according to EN 61591	
▪ Sound regulation according to EN 60704-2-13	
▪ Airflow speed 1 (m ³ /h) / Max Pressure speed 1 (Pa)	304 / 190
▪ Airflow speed 2 (m ³ /h) / Max Pressure speed 2 (Pa)	406 / 240
▪ Airflow speed 3 (m ³ /h) / Max Pressure speed 3 (Pa)	550 / 266
▪ Sound power speed 1 (dB(A)) / Sound pressure speed 1 (dB(A))	51 / 40
▪ Sound power speed 2 (dB(A)) / Sound pressure speed 2 (dB(A))	57 / 46
▪ Sound power speed 3 (dB(A)) / Sound pressure speed 3 (dB(A))	63 / 52

Technical specifications

▪ Maximum power	201
▪ Voltage (V)	220-230
▪ Frequency (Hz)	50
▪ Length power supply cord (m)	1,2
▪ Power consumption in off-mode (Po) (W)	0,00
▪ Net weight (kg)	24,2



