

HR1060|05

HR Build Under 60 cm Stainless steel

Functions & features

Control method	Push buttons
■ Number of speeds	1
■ Motor	Without
Sound absorber	Without
■ Auto stop	-
■ Number of grease filters	1
■ Grease filter cleaning indication	-
Recirculation filter cleaning indication	-

Dimensions

Product dimensions exhaust (WxDxHmin-Hmax) (mm)	598 x 520 x -
Product dimensions recirculation (WxDxHmin-Hmax) (mm)	598 x 520 x -
 Advised mounting height ceramic hobs (Hmin-Hmax) (mm) 	650 - 750
Advised mounting height gas and induction hobs (Hmin-Hmax) (mm)	650 - 750
Diameter outlet (mm)	125
Position exhaust	Тор

Lighting


Functional lighting type	Halogen
■ Dimmable light	-
Soft-ON/OFF	-
■ Total energy consumption functional light (W)	28


Airflow and noise level

 Airflow (m³/h) measured according to 	
Sound regulation according to EN 60704-2-13	
Sound power speed 1 (dB(A)) / Sound pressure speed 1 (dB(A))	45 / 34


Technical specifications


Maximum power	128
Voltage (V)	220-230
Frequency (Hz)	50





2





HR1060|05